by Program Studi Teknik Mesin


**Submission date:** 26-Sep-2022 02:31PM (UTC+0700)

**Submission ID:** 1909243879

**File name:** Analysis\_of\_Physical\_and\_Mechanical\_Properties\_of.pdf (1.17M)

Word count: 4605

Character count: 24386



**3** 112



### **Abstract:**

Buckets are the most important component in backhoe construction, the bucket functions as a digger and carrier component in an excavator. Due to the heavy working media of the excavator so that this component is the most easily damaged part, damage that often occurs is wear caused by friction arising so that the thickness of the bucket is reduced which can eventually cause cracks in the bucket and in continuous use can cause the bucket to crack and broken. Cladding method is done to shorten the time or simplify the repair process is to directly patch the damaged part with a welding layer and then do the grading using a grinding. This

study aims to determine the physical and mechanical properties of the material from the cladding process when compared with the raw material, the variations used are raw material, cladding with filler welding, and cladding with plates. The welding process is carried out with GMAW (Gas Metal Arc Welding) and low carbon steel. Welding results will be tested tensile strength, bending strength, impact test, hardness test, chemical composition, and corrosion rate. From the hardness test results showed that the weld metal from plate variation has the highest hardness value of 443 VHN. From the results of tensile testing the basic material has the highest value with 359.08 MPa. From the bending test results the highest value obtained from filler verification with 494.01 Mpa and the highest impact price obtained from the plate variation cladding method with a value of 1.49 J / mm2



Info:

Analysis of Physical and Mechanical Properties of Backhoe's Bucket Repairment with Cladding Methode | Scientific.Net 2/26/22, 5:58 AM Key Engineering Materials (Volume 841) Periodical: Prof. Mosbeh Kaloop Edited by: Pages: 254-258 https://doi.org/10.4028/www.scientific.net/KEM.841.254 DOI: Cite this paper Citation: May 2020 Online since: Yustiasih Purwaningrum\*, Muhammad Hafiz, Risky Authors: Suparyanto Cladding, Corrosion Rate, Hardness, Tensile Strength Keywords: RIS, BibTeX Export: 39,00€ Price: **Request Permissions** Permissions: ★ f in 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 
 ★ 

 ★ 

 ★ 

 ★ 

 ★ 

 ★ 

 ★ 

 ★ 

 ★ 

 Share:

# References >

## Cited by >

# Related Articles >



<sup>\* -</sup> Corresponding Author



IMPRINT

PRIVACY POLICY

**SITEMAP** 

**ALL CONFERENCES** 

**ALL SPECIAL ISSUES** 


**ALL NEWS** 








2 Scientific.Net is a registered brand of Trans Tech Publications Ltd © 2022 by Trans Tech Publications Ltd. All Rights Reserved





Universidad Carlos III de Madrid, IMDEA Materials; Av. Universidad 30, Leganés, 28911, Spain;



### Prof. Aldo Roberto Boccaccini

University of Erlangen-Nürnberg, Institute of Biomaterials, Department of Materials Science and Engineering; Cauerstrasse 6, Erlangen, 91058, Germany;

### Prof. Mónica Campos

### **ORCID**

University Carlos III de Madrid , Department of Materials Science and Engineering; Av. Universidad 30 , Leganés-Madrid, 28911, Spain;

### <mark>2</mark> Dr. Li Chang

University of Sydney, School of Aerospace, Mechanical and Mechatronic Engineering; Sydney, Australia, 2006;

### Prof. Yi Bing Cheng

### **ORCID**

Monash University, Department of Materials Science and Engineering; PO Box 197, Caulfield East, Australia, 3145;

### Prof. Ilaria Cristofolini

### **ORCID**

University of Trento, Department of Industrial Engineering; Via Sommarive 9, Povo, 38123, Italy;

### **Prof. Robert Danzer**

Montanuniversität Leoben, Institut für Struktur- und Funktionskeramik; Peter-Tunner-Strasse 5, Leoben, A-8700, Austria;

# Prof. Suong Van Hoa

Concordia University, Department of Mechanical and Industrial Engineering; 1455 Demaisonneuve West # EV 4-145, Montreal, Canada, H3G1M8;

### Prof. Xiao Zhi Hu

University of Western Australia, School of Mechanical and Chemical Engineering; Perth, Australia, WA 6009;

### Prof. Mohamed A. Taha

Ain-Shms University, Department of Design and Production Engineering, Faculty of Engineering; Khalifa El-Maamon st, Abbasiya sq., Cairo, Egypt, 11566;

### Prof. Alejandro Ureña Fernandez

Universidad Rey Juan Carlos (URJC), Department of Materials Science and Engineering; Tulipan s/n 28933, Mostoles, Madrid, Spain;

### Prof. Dragan P. Uskokovic

Institute of Technical Sciences of the Serbian Academy of Sciences and Arts; Knez Mihailova 35/IV, Belgrade, Serbia;

### Prof. Maria Teresa Vieira

### **ORCID**

Universidade de Coimbra, ICEMS - Instituto de Ciência e Engenharia de Materiais e Superficies ; Pólo II-Pinhal de Marrocos, Coimbra, 3030-788, Portugal;

### 2 Prof. Zhi Rui Wang

University of Toronto, Department of Materials Science and Engineering; 184 College Street, Toronto, Canada, M5S 3E4;

### **Prof. Ming Xing Zhang**

**DISTRIBUTION & ACCESS** 

University of Queensland, School of Mechanical and Mining Engineering; St. Lucia, Queensland, Australia, QLD 4072;

# FOR PUBLICATION INSIGHTS DOWNLOADS ABOUT US POLICY & ETHICS CONTACT US IMPRINT PRIVACY POLICY SITEMAP ALL CONFERENCES



**ALL NEWS** 



**ALL SPECIAL ISSUES** 



2 Scientific.Net is a registered brand of Trans Tech Publications Ltd © 2022 by Trans Tech Publications Ltd. All Rights Reserved

# Material Engineering and Application II

# **Table of Contents**

### Preface

# **Chapter 1: Engineering Materials**

Effect of Plating Thickness on Fatigue Strength of Galvanized Steel K. Hasegawa, T. Hayashi, M. Morita and S. Motoda	3
Influence of Nano-Silica Dosage on Properties of Cement Paste Incorporating with High Calcium Fly Ash  Suggest P. Litangian and P. Chindangairt	0
Suwan, P. Jitsangiam and P. Chindaprasirt	9
Mechanical and Shrinkage Behaviors of Ductile Fiber-Reinforced Polymer Repair Mortar Y. Han and J.L. Luo	14
Development of a TAPE-Agar Liquid Gel Bandage	
F.M. Bautista, M.R.H. Tam, K.A.D. Wong and T. Tumolva	20
Frequent Start-Stop Test Study of Graphene Coatings on Journal Bearings B. Wang, Y.F. Zhang and Z.W. Yin	26
A New Technology to Prevent the Formation of Limescale in Hot Water Supply Systems M. Jalilova, A. Jalilova, G. Feyziyeva and M. Azimova	36
Development of a CuFe <sub>2</sub> O <sub>4</sub> - Reduced Graphene Oxide-Based Electrochemical Sensor for	
Malathion  A.T. Battad, J.G. Estacio, J.L.C. Indiongco and M.J.L. Mopon	41
Nano-Crystallization of Steel Surface by Slide-Burnishing Kato, K. Yamamoto and K. Yasunaga	48
Numerical Simulation of Material Plastic Deformation Using the Drawing Forming Process	
of Contoured Internal Surface Tubes  Necpal, E. Hodúlová and M. Martinkovič	54
Solvent Absorption and Dissolution Kinetics Modelling for the Chemical Recycling of Waste Plastic Laminates	
M.S.P. Deang, R.I.C. Alindayu, K.V.H. Escasa, G.M.G. Riña and T. Tumolva	59
Feasibility of Paper Production from Oil Palm Trunk Using Arrowroot Flour as a Binder Phruksaphithak and J. Wangprayot	64
Study on Morphology Features and Mechanical Properties of Nanofibers Films Prepared by	
Different Composite Electrospinning Methods  He, H. Wang, L.X. Huang, P. Wang and W. Gao	70
Studying the Stability and Conductivity of the Composite Films via Electrospinning/Spray	70
Process	
X. Huang, H. Wang, F.Y. Fang, P. Wang and W. Gao	76
Electrospinning/Spray: The Interaction between Graphene Nanosheets and Different	
Nanofibers Z. Chen, H. Wang, F.Y. Fang, H. Mei and L. Wang	82
Tensile Properties of Cellulose-Filled Recycled Thermoplastic Composite Filaments for 3D	02
Printing	
M. Hyvärinen and T. Kärki	87
3D Reconstruction of Microstructure for Centrifugal Casting Babbitt Lining of Bimetallic	
Bearing Based on Mimics Dong, Z.W. Yin, H.L. Li, Y. Mao and G.Y. Gao	94
X-Ray Powder Diffraction Data and Crystal Refinement of Ternary Compound Ti <sub>4</sub> ZrSi <sub>3</sub> L.Q. Liang, Y.Y. Wei and D.G. Li	99
The Green Preparation of Cellulose Fibrils from Oil Palm Leaf Stalk Fibers for Hydrogel	
Applications Srirachya and A. Nido	103
Evaluation of Recycled Aggregate (RAP) Presence Impact under Indirect Tensile Strength of Bitumen Stabilized Mix with Foamed Asphalt for a Base Layer	100
M.A.V. Guzmán, H.D. Alamilla, E.M.A. Guzmán, W.M. Molina, H.L.C. García and R.R. Ruiz	108

Scanning Electron Microscope in Rocks and their Comparison with Physical-Mechanical Properties	
M.A.N. Seras, F.J.D. Mota, E.M.A. Guzmán, W.M. Molina, H.L.C. García, J.G.T. Ruiz and A.G. Torres	114
Natural Additive to Retard the Setting of a Mortar and Increase its Resistance D. González, L.A.G. Luna, E.M.A. Guzmán, W.M. Molina, H.L.C. García and J.A.V. Perez	119
Electrochemical Synthesis of Hydroxyapatite Nanosheet-Assembled Porous Structures with Bipolar Membrane	124
A. Nur, A.W. Budiman, A. Jumari, N. Nazriati and F. Fajaroh	124
The Comparison between Mechanical Properties of Laser-Welded Ultra-High-Strength Austenitic and Martensitic Steels  M. Keskitalo and A. Järvenpää	132
Mechanical Properties of Concrete Using Treated Recycled Concrete Aggregate in Marine	102
Environment  Ismail and M. Ramli	138
Failure Analysis of Spur Gears Used in Transmission System Applied on a Hand Tractor pusaini, D.M. Dawud, T.E. Putra and N. Ali	144
Biofuel Production from Jatropha Bio-Oil Derived Fast Pyrolysis: Effect of Catalysts	
Supported T. Rodseanglung, T. Ratana, M. Phongaksorn and S. Tungkamani	150
Experimental Investigation and Modelling of Claystone from Mae Moh Coal Mine, Thailand	
Wongchana and P. Jitsangiam	155
Preliminary Investigation of Crushed Rock-Based Geopolymer for Road Applications H. Thongchua, P. Jitsangiam, T. Suwan, D. Rinchumphu, S. Kwunjai and P. Chindaprasirt	161
Hemp Fiber Reinforced Geopolymer Composites: Effects of NaOH Concentration on Fiber Pre-Treatment Process	
P. Maichin, T. Suwan, P. Jitsangiam and P. Chindaprasirt	166
Crushed Rock Geopolymer as a Future Road Construction Material: An Evaluation on Strength Performance and Compaction Characteristics S. Kwunjai, P. Jitsangiam, T. Suwan, D. Rinchumphu, H. Thongchua, P. Chindaprasirt and S. mpattagul	171
Response Behavior of Local Surface Failure due to Repetitive Impact of Stainless Steel  1. Sukpat and K. Tuchinda	177
Study of Properties of 3D Printed Short Carbon Fiber Composite	1,,,
Saithongkum and K. Tuchinda	182
High Purity Lime as an Ecologic Alternative for Construction Mortars and Pastes E.G. Navarro Mendoza, J.A. Bedolla-Arroyo, A.S. Calvillo, E.M.A. Guzmán, V.H. Blancas- Herrera, W.M. Molina and H.L.C. García	188
Cemented Mortar Matrices Densified with Organic Additions L.C. Velázquez, E.M.A. Guzmán, W.M. Molina, H.L.C. García, M.C.G. Chiquito and M.A. Sánchez	193
Evaluation of the Electrical Resistivity, Ultrasonic Pulse Velocity and Mechanical Properties in Portland Cement Pastes Type II	100
J.A.V. Perez, E.M.A. Guzmán, W.M. Molina, H.L.C. García, I.T. Moreno and M.A. Sánchez  Characterization of Hydraulic Concrete with Polystyrene-Based Emulsion	198
M.C.G. Chiquito, E.M.A. Guzmán, W.M. Molina, H.L.C. García and N.D. González	203
Preparation and Performance Study of Fluorosilicone Oligomer Anti-Sticking Coatings D.B. Guan, X.J. Zhai, Y.N. Biansai, B.J. Cao, Y.F. Zhu and J.L. Li	209
The Effect of Alloying on the Fractional Composition, Shape and Grain Size Distribution of the Structure Alloy GAP the Fe-Nd-B System V.A. Chaika, V.V. Savin, M. Sorokovikov and A. Marikhin	214
Optimization of Methylene Blue Adsorption via Functionalized Activated Carbon Using Response Surface Methodology with Central Composite Design Saafie, M.F.R. Samsudin and S. Sufian	220
Rejection Rate Reduction of the Automotive Thermoplastic Parts in Injection Moulding Using Response Surface Methodology	
H.R. Ong, I.M. Shah, W.M.E. Iskandar, M.M.R. Khan, C.S. Hong, R. Ramli and M.K.A. Mohamed	225

1	
Simulation of Gap Flow Field in EDM Process Uesd Oil-in-Water Working Fluid W.J. Chang, Y.Y. Xi and H.W. Li	232
Synthesis, Preparation and Characterization of Amine-Induced Bacterial Cellulose-	
Poly(Vinyl Alcohol) Semi-Interpenetrating Network Hydrogel E. Arikibe, R. Lata and D. Rohindra	238
Effect of Substrate Temperature on the Electronic Properties of MgO Thin Films on Si	
(100) Grown by Electron Beam Evaporation R. Denny, T. Firmansyah, V. Gustiono and S.S. Lee	243
Button of Hydroxyapatite Composite for Craniotomy Flap Fixation: Fabrication and	243
Mechanical Properties	
A. Raksujari and S. Punyanitya	248
Analysis of Physical and Mechanical Properties of Backhoe's Bucket Repairment with Cladding Methode	
Y. Purwaningrum, M. Hafiz and R. Suparyanto	254
Fabrication Study of Cu-C-Ni for EDM Electrode by a Sintering Technique  Janmanee, A. Muttamara, R. Saodaen and A. Rodchanarowan	259
Synthesis and Characterization of Active Biocarbon Material for Use in Cosmetics and	
Personal Care Products A. Palsan, J.Y. Lim and A. Nor Asfaliza	266
Characterization of Adsorbents Derived from Palm Fiber Waste and its Potential on	
Methylene Blue Adsorption  A Zulkania, M. Iqbal and Syamsumarlin	273
Potential Activity Evaluation of Phosphorus on CoMo/Al <sub>2</sub> O <sub>3</sub> -TiO <sub>2</sub> Catalysts to Co-	273
Processing Model	270
Rodseanglung and J. Paksamut  Investigation of the Tensile and Flexural Behavior of Polylactic Acid Based Jute Fiber Bio	278
Composite	
M. Aadithya, V.K. Kirubakar, T. Aakash and C. Senthamaraikannan	283
Fatigue and Fracture Mechanism of Aluminum-Carbon Fiber Reinforced Hybrid Composites	
M.M. Rahman and M.S. Ferdous	288
Fatigue-Corrosion of High Strength Steels in Synthetic Seawater under Cathodic Protection S. Lorenzi, C. Testa, M. Cabrini, F. Carugo, L. Coppola and T. Pastore	294
Effect of Cr and Si Contents on the Magnetic and Mechanical Properties of Fe-Cr-Si Alloys	
<b>by MIM Process</b> M. Kimura, T. Shimizu and H. Watari	300
Microstructure and Mechanical Properties of Laser Welded 316L SLM Parts	
T. Rautio, J. Mäkikangas, M. Jaskari, M. Keskitalo and A. Järvenpää	306
The Effect of Calcination Temperature on Metakaolin Characteristic Synthesized from Badau Belitung Kaolin	
R. Ulfiati, D. Dhaneswara, J.F. Fatriansyah and S. Harjanto	312
Flavor Quality Changes of Turbot (Psetta maxima) Stored at -2 and 0°C	217
L. Zhao, Y.M. Yin, Y. Liu, Y.X. Xu, X.P. Li and J.R. Li  Investigation on Mechanical Behavior of Sisal Fiber Reinforced Polylactic Acid and	317
Sisal/Epoxy Composites	
S. Dhannush, S. Aushwin, A.R. Arunagiri and C. Senthamaraikannan	322
Evaluation of Mechanical Properties of Sugarcane Reinforced Hybrid Natural Fibre Composites by Conventional Fabrication and Finite Element Method	
D.S. Ram, P.N.B. Kumar, R.S. Kumar and B.V. Ramnath	327
Study of Deep Cryogenic Treatment Process Effect on Microstructure and Properties of	
CuBeZr Alloy Wannaprawat and K. Tuchinda	335
Casting of High Aluminum Content AM Series Magnesium Alloys by Using a Horizontal	
Twin Roll Caster Tozuka, K. Seki, H. Watari and T. Haga	340
Estimation of Cold Roll Forming Characteristics of Wrought Magnesium Alloy with	340
Tension-Compression Asymmetry	24
H Kobayashi H Tozuka and H Watari	346

# **Chapter 2: Materials Properties and Application**

Analogy of Non-Destructive Tests for the Detection of Defectologies in Aluminium Cylinder Heads	
S.S. Valencia, L.C. Galárraga, H.C. Terán and O. Arteaga	355
Surface Roughness Prediction Based on Acoustic Emission Signals in High-Precision Diamond Turning of Rapidly Solidified Optical Aluminum Grade (RSA443) Z. Hweju and K. Abou-El-Hossein	363
Flow Field Analysis and Experimental Investigation of Electrochemical Etching Y.L. Chen, C.H. Guo, P.X. Chen, Z. Liu and A.S. Lv	369
3D FEM Study of the Flow Uniformity of Flat Polypropylene Film/Sheet Extrusion Dies D. Igali, A. Perveen, D.M. Wei, D.C. Zhang and A. Mentbayeva	375
Prediction of the Fatigue Life of the SAE 5160 Carbon Steel Coil Spring Based on Strain-	
Life Approach T.E. Putra, Husaini and H. Prakasa	381
Design and Optimization of Die Body for Polymer Extrusion T. Saparov, U. Belgibay, D.C. Zhang, D.M. Wei, C.N. Sun, A. Mentbayeva and A. Perveen	387

### ResearchGate

 $See \ discussions, stats, and \ author \ profiles \ for \ this \ publication \ at: \ https://www.researchgate.net/publication/342025519$ 

# Analysis of Physical and Mechanical Properties of Backhoe's Bucket Repairment with Cladding Methode

Preprint	· June 2020		
CITATION S		READS 96	
3 author	s, including:		
1	Yustiasih Purwaningrum Universitas Islam Indonesia		
	18 PUBLICATIONS 20 CITATIONS  SEE PROFILE		

All content following this page was uploaded by Yustiasih Purwaningrum on 09 June 2020.

The user has requested enhancement of the downloaded file.

Submitted: 2019-12-04 Accepted: 2019-12-04

Online: 2020-05-05

Yustiasih Purwaningrum<sup>1,a\*</sup>, Muhammad Hafiz<sup>1</sup> and Risky Suparyanto<sup>1</sup>

<sup>1</sup>Mechanical Engineering Department, Islamic University of Indonesia, Jalan Kaliurang Km 14,5, Ngemplak Sleman Yogyakarta, Indonesia

ayustiasih.purwaningrum@uii.ac.id

Keywords: Cladding, Tensile strength, Corrosion rate, Hardness

Abstract. Buckets are the most important component in backhoe construction, the bucket functions as a digger and carrier component in an excavator. Due to the heavy working media of the excavator so that this component is the most easily damaged part, damage that often occurs is wear caused by friction arising so that the thickness of the bucket is reduced which can eventually cause cracks in the bucket and in continuous use can cause the bucket to crack and broken. Cladding method is done to shorten the time or simplify the repair process is to directly patch the damaged part with a welding layer and then do the grading using a grinding. This study aims to determine the physical and mechanical properties of the material from the cladding process when compared with the raw material, the variations used are raw material, cladding with filler welding, and cladding with plates. The welding process is carried out with GMAW (Gas Metal Arc Welding) and low carbon steel. Welding results will be tested tensile strength, bending strength, impact test, hardness test, chemical composition, and corrosion rate. From the hardness test results showed that the weld metal from plate variation has the highest hardness value of 443 VHN. From the results of tensile testing the basic material has the highest value with 359.08 MPa. From the bending test results the highest value obtained from filler verification with 494.01 Mpa and the highest impact price obtained from the plate variation cladding method with a value of 1.49 J / mm2.

### Introduction

Heavy equipment is equipment that are widely used in building construction or mining. Increasing infrastructure development and mining has led to higher demand for heavy equipment. The type of heavy equipment that is most often used is a digger or also known as an excavator. Excavators are used to dig soil or rocks, including types of excavators are front shovels, backhoes, draglines and clamshells. The construction of a backhoe excavator is divided into several parts, including: buckets that are used as digging containers, arms of the backhoe, the wheelhouse of the operator, the engine as a motor, and the shoe track frame that functions as a wheel on the excavator.

Bucket is the most easily damaged component. Damage that often occurs is wear caused by friction that arises so that the bucket thickness is reduced which can eventually cause bucket cracks and in continuous use can cause the bucket to crack and break. Bucket replacement costs and takes a long time so if there is damage to the bucket, repairs that can be done is to cut the damaged part and replace with a new steel plate using welding. However, what is generally done by the company to shorten the time or simplify the repair process is to directly patch the damaged part with the weld layer. After all the damaged parts are covered with welds, then grading is done using a grinding. Repairing buckets with this methode can minimize the unit in a breakdown condition. This repaired methode is called cladding.

Cladding is a process where material covers or coats another either internally or externally [1]. Cladding can be done by forming processes such as rolling and casting, and joining processes such as welding [2]. Different types of arc welding like Shielded Metal Arc Welding (SMAW), Gas Tungsten Arc Welding (GTAW), Gas Metal Arc Welding (GMAW), Flux Cored Arc Welding (FCAW) can successfullly produce cladding. GMAW is widely accepted by industry to produce weld cladding [3 4].

The advantages of Gas Metal Arc Welding (GMAW) are high productivity, low cost and high reliability [5 6]. The shape of cladding influences mechanical properties of cladding steel welded [7].

### Experimentals

**Welding System.** This experimental used SWRM 1008 Low Carbon Steel as a raw material. The spectrometric analysis of the specimen was done by using Spectromax and the chemical compositions of base metal and welding metal were reported in Table 1. The welding processes was carried out by GMAW (Gas Metal Arc Welding) with electrode ER 70S-6 as a filler metals. The welding parameter is shown in Table 2.

Table I C	hemical (	Composition	of SWRN	1 1008 Low	Carbon Steel	

Element	Fe	С	Mn	P	Si	Cu	S	Ni	Cr	Мо
Raw Material	99.5318	0.0666	0.2537	0.0308	0.0117	0.1400	0.0156	0.0063	0.0229	0.0052
Filler	97.7337	0.0647	1.0909	0.1640	0.6826	0.2642	0.0163	0.0392	0.0467	0.0014

Table 2 Welding Parameter

Material	Low Carbon Steel (SWRM 1008)			
Dimension	250 mm x 250 mm x 1.36 mm			
Type	GMAW			
Electrode	AWS A5.18 ER 70S-6, diameter			
	1.2 mm			
Current	80 A			
Welding rate	2.7 mm/s			
Voltage	16 Volt			
Wire feed rate	1 m/min			
Welding gas	Argon			

The variation buttering of welding that used were filler and plate. The schematic of cladding is shown in Fig. 1. In variations of cladding with filler, the surface of the raw material with dimensions of 250x250 mm welded on its surface is then flattened with a grinding. The other variation, cladding with plate, a plate measuring 250 mm x 10 mm was added to the top of the base plate in a row with a gap of about 1 mm. In the plate variation the welding process is carried out only on gaps that have been prepared in advance. This welding is carried out in a continuous direction (sequence) to avoid large deformations.



Fig. 1 Variation Cladding Steel Welded

**Joints Characterizations.** Mechanical properties of cladding weld steels obtained from tensile strength and bending strength testing. The tensile strength of cladding steel welded were tested by Universal Testing Machine. The specimens tested were according to the standar ASTM E - 8M. Three point bending method used to measure the bending strength of buttering weld steels. This test is carried out using standards JIS Z2204.

Corrosion and Vickers microhardness testing is carried out to obtain physical properties of buttering weld steels. Vickers indentor under 200 gr force for 10 seconds was used to investigate the hardness of buttering weld steels.

$$corrosion\ rate = \frac{W}{{}^{TSA}x\frac{T}{365}}$$

W = weight loss (gram)

TSA = total surface area (mm<sup>2</sup>)

T = time of exposure (days)

### **Results and Discussion**

**Tensile Strength.** Fig. 2 shown the tensile strength and elongation of cladding steel. The experimental results showed that the method of cladding steel welded to repair bucket decreased tensile strength and elongation of material. The decline of tensile strength in a row as follows: cladding with filler = 273.89 MPa and cladding with plate = 318.89 MPa.




Fig. 2 Tensile Strength of Cladding Steel Welded

**Bending Strength.** As we can see from Fig. 3 the weld metals with filler cladding has a highest bending strength. The values of bending strength of this variation is 494.01 Mpa, this value is 31.06 % more than raw material.




Fig. 3 Bending Strength of Cladding Steel Welded

**Corrosion.** The value of corrosion rate can we seen at Fig. 4. From this diagram, it was found that filler specimens had the best resistance to corrosian with a value of 1.43 mmpy slightly different from raw material specimens which had an average value of 1.54 mmpy. whereas specimens with plate cladding variations have the lowest resistance of corrosion with a value of 4.24 mmpy.




Fig. 4 Corrosion rate of Cladding Steel Welded

**Hardness.** Variation of hardness from buttering steel is shown in Fig. 5. The Fig.1 shows that hardness of welding metal has highest values. The hardness number of weld metals are 443 VHN for plate cladding and 423 VHN for filler cladding.




Fig. 5 Hardness Number of Cladding Steel Welded

### Summary

Based on the results of tests that have been carried out in research into the repaired of the backhoe bucket with cladding method with variations in the welding process with variations of filler and plate, the following conclusions can be drawn:

- The chemical composition of cladding steel welded such as S, Ni, Si, Cr, Mn, N, Cu and Ti has increased, but the element C has decreased. The reduction of element C causes the mechanical properties of the filler variation to increase, this is seen in bending testing
- Cladding with plate variations have better mechanical properties because have better hardness, tensile strength and strain values than filler variations.

• The corrosion rate on cladding steel weled with plate variations has very poor corrosion resistance with a value of 4.2429 mmpy compared to raw material specimens and filler variation with a value of 1.4358 mmpy.

### References

- [1] M. K. Saha, S. Das, Gas Metal Arc Weld Cladding and its Anti-Corrosive Performance-A Brief Review, Athens J. Technol. Eng. 5(2) 155-174.
- [2] J. R. Davis, Davis&Associates, Stainless Steel Cladding and Overlays, ASM Specialty Handbook: Stainless Steels, 06398G. (1984).
- [3] W. Lucas, Arc surfacing and cladding processes to enhance performance in service and to repair worn components, Welding Metal Fabrication. 62(2) (1994) 55-60.
- [4] T. Kannan, J. Yoganandh, Effect of process parameters on clad bead geometry and its shape relationships of stainless steel claddings deposited by GMAW, Int. J. Adv. Manufact. Technol. 47(9-12) (2010) 1083-1095.
- [5] F. Kjeld, Gas metal arc welding for the collision repair industry, American Welding J. 70(4) (1991) 39-46.
- [6] K.A. Lyttle, GMAW-A versatile process on the move, American Welding J. 62(3) (1983) 15-23.
- [7] D. C. Montgomery, Design and Analysis of Experiments, John Wiley& Sons, Inc. (1984).

$\cap R$	IGII	NAI	ITY	RF	PORT

23% SIMILARITY INDEX

25%

14%

3%

MILARITY INDEX INTERNET SOURCES

**PUBLICATIONS** 

STUDENT PAPERS

### **PRIMARY SOURCES**



searchworks.stanford.edu

Internet Source

16%

2

repository.unair.ac.id

Internet Source

7%

Exclude quotes

On

Exclude matches

< 3%

Exclude bibliography On